

Issue Date: 26 Aug 2019
 Version No.: 02 (Supersedes Version: 01)
 Last Revision Date: 11 Jun 2019
 Product No.: -

Page 1 of 7

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

1.1 **Product Name:** UNIVERSAL DIGITAL THERMAL DEVELOPER
 1.2 **Product Code:** 872264
 1.3 **Recommended Use and Restriction on Use:** Developer for printing plates.
 1.4 **Manufacturer:** FUJIFILM Asia Pacific Pte. Ltd.
 UEN: 199301558N
 1.5 **Address:** 15 Tuas Avenue 7
 Singapore 639270
 1.6 **Business Phone Number:** (65) 6862 2116 (Operating hours: 0830-1730 hours Mondays-Fridays)
Fax: (65) 6861 4829
Emergency Phone Number: (65) 6863 8753

SECTION 2: HAZARDS IDENTIFICATION

2.1 GHS Classification:

Hazard Class	Hazard Category	Hazard Statement
Corrosive to metals	Category 1	May be corrosive to metals.
Skin corrosion/irritation	Category 2	Causes skin irritation.
Serious eye damage/irritation:	Category 2	Causes serious eye irritation.

2.2 GHS label elements

Pictograms:



2.3 Signal Word: Warning

2.4 Precautionary Statements:

Prevention

Keep only in original container.
 Wash your hands and face thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.

Response

Absorb spillage to prevent material damage.
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation occurs: Get medical advice/attention.
 Take off contaminated clothing and wash before reuse.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.

Storage

Store in corrosive resistant container with a resistant liner.

2.4 Disposal:

None.

Other Hazards Which Do Not Result in Classification

Primary Hazards

None

Issue Date: 26 Aug 2019
Version No.: 02 (Supersedes Version: 01)
Last Revision Date: 11 Jun 2019
Product No.: -

Page 2 of 7

Specific Hazards

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance or Preparation: This product is a mixture.

Chemical Name	CAS No.	% by Weight
Water	7732-18-5	85 - 95
Sodium metasilicate	6834-92-0	5 - 15

SECTION 4: FIRST-AID MEASURES

4.1 Inhalation:

- Move the victim into the fresh air, keep him or her warm and quiet, cover with a blanket, and send for immediate medical assistance.
- If the victim is not breathing or is breathing very weakly, loosen his or her clothing in order to secure an airway and begin artificial respiration.
- If the casualty is unconscious, but breathing, or is conscious but experiencing breathing difficulties, the provision of oxygen is effective. It is preferable to do this under medical supervision.
- No medicine other than oxygen may be dispensed. No food may be given to the victim without the physician's direction.

4.2 Skin Contact:

- If it is spilled on the skin, wash off with copious amounts of soap and water.
- Remove the contaminated clothes, shoes, etc., immediately. Cut the clothing off if necessary. Subsequently, rinse the skin with cool or tepid running water for at least 30 minutes.
- Immediate medical attention is required.

4.3 Eye Contact:

- If a contact lens is in place, remove it and wash the eye with warm running water for at least 15 minutes, unless the lens is firmly attached to the eye. Use physiological saline if it is readily available.
- Do not stop rinsing the eye. During the rinse, open the eyelid with your fingers so that water can reach under the eyelid. Send for an ophthalmologist immediately. An ophthalmological examination is absolutely essential because the possibility exists that there may be after effects even if there are no immediate pain or vision problems.

4.4 Ingestion:

- If it is swallowed, call a doctor immediately.
- Do not attempt to make the victim vomit.
- Rinse the mouth out thoroughly with water.
- Give the casualty 1-2 glasses of water to dilute the quantity of the substance in the stomach. (If milk is readily available, this can be given to the casualty after the water.)
- If the victim vomits of his/her own accord, bend his/her body so as to prevent vomit from entering the lungs. After vomiting, allow the victim to drink more water. Keep the victim warm and send for a doctor immediately and show SDS or label.

4.5 Likely Acute or Delayed:

- None

4.6 Note to Physician:

- None

4.7 Protection of First-Aid Providers:

- First-aid personnel should wear personal protection equipment when assisting the casualty.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable Fire-Extinguishing Media:

Issue Date: 26 Aug 2019
Version No.: 02 (Supersedes Version: 01)
Last Revision Date: 11 Jun 2019
Product No.: -

Page 3 of 7

- Foam (alcohol-resistant foam), powder, and carbon dioxide are effective fire-extinguishing agents.

5.2 Unsuitable Extinguishing Media:

- None under normal conditions.

5.3 Hazardous Combustion Products:

- None

5.4 Special Protective Actions for Fire Fighters:

- Cool the container(s) surface that is exposed to fire by spraying the surface with water.
- When fighting the fire, wear protective equipment (i.e., respiratory apparatus, chemical protection suit, gloves, boots, goggles, mask, etc.) as needed to avoid inhaling and/or skin contact with the chemical substance. Extinguish from the upwind direction.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment, and Emergency Measures:

- Wear protective equipment (i.e., respiratory apparatus, chemical protection suit, gloves, boots, goggles, mask, etc.) as needed to avoid inhaling and/or skin contact with the chemical and/or vapours, if any. Work upwind, if possible.
- See Section 8 of this SDS for Personal Protective Equipment.

6.2 Environmental Precautions:

- Do not allow to enter drains, sewers or water courses.
- The chemical substance in question should not be released into the environment (water, soil).

6.3 Spill Containment and Cleaning Up:

Minor Spills

- Avoid chemical contact by using personal protective equipment.
- Clean up spills immediately.
- Contain and absorb spill with sand, earth or other suitable absorbent material.
- Place spilled material in clean, dry, sealable, labelled container for disposal.

Major Spills

- Clear area of personnel and move upwind.
- Call SCDF or local Fire Brigade.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or other suitable absorbent material.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise local Environmental Agency or Authority.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for Safe Handling:

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.

Issue Date: 26 Aug 2019
Version No.: 02 (Supersedes Version: 01)
Last Revision Date: 11 Jun 2019
Product No.: -

Page 4 of 7

- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

7.2 Conditions for Safe Storage:

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Keep out of reach of children.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters/Occupational Exposure Limits:

Ingredient	CAS No.	PEL/OEL	Source
Sodium metasilicate	6834-92-0	Not established	Not established

8.2 Appropriate Engineering Controls:

- Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator.

8.3 Personal Protective Equipment:

- Use the following protective equipment as needed:
- **Respiratory Protection:** Self contained breathing apparatus.
- **Eye Protection:** Wear approved safety goggles.
- **Hand Protection:** Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.
- **Skin Protection:** Apron and long sleeves are recommended. Wear suitable protective clothing.
- **Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance Physical State:	Slight hazy liquid	
9.2 Colour:	Colorless	
9.3 Odour:	Odourless	
9.4 Odour Threshold:	Not applicable	
9.5 Property	Value	Notes
Melting Point	0°C	
Boiling Point	100°C	
Flash Point	Not applicable (Not flammable)	Closed cup
Explosive Limit	Not applicable	Lower limit
Explosive Limit	Not applicable	Upper limit
Vapour Pressure	Not applicable	At 20°C
Vapour Density	Not applicable	Air=1
Relative Density	1.07 - 1.08	25°C
Solubility in Water	Completely soluble	Water at 20°C
Solubility (Other)	Not applicable	
Partition Coefficient: n-octanol/water	Not applicable	
Viscosity	Not applicable (like water)	
pH	12.90 - 13.1	25°C
Evaporation Rate	Not applicable	Butyl Acetate = 1
Flammability (Solid, Gas)	Not applicable	
Auto-Ignition Temperature	Not applicable (Not flammable)	
Decomposition Temperature	Unknown	

Issue Date: 26 Aug 2019
 Version No.: 02 (Supersedes Version: 01)
 Last Revision Date: 11 Jun 2019
 Product No.: -

Page 5 of 7

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity/Incompatible Materials:**
- Acids, metals.
- 10.2 Chemical Stability:**
- Stable under normal temperature and pressure.
- 10.3 Possibility of Hazardous Reaction:**
- No hazardous reactions are foreseeable in normal conditions of use and storage
 - Sodium metasilicate may react dangerously with fluorine and lithium
- 10.4 Conditions to Avoid:**
- Excessive heat. Freezing.
- 10.5 Hazardous Decomposition Products:**
- Information not available

SECTION 11: TOXICOLOGICAL INFORMATION

- 11.1 Acute Toxicity on Product Mixture:**
- Oral LD50 Rat 600 mg/kg
 - Dermal LD50 No data available.
 - Inhalation LC50 No data available.

11.2 Acute Toxicity on Ingredients:

Chemical Name	CAS No.	Acute Oral (LD50 mg/kg)	Test Animal
Sodium metasilicate	6834-92-0	600	Rat

- 11.3 Skin Corrosion/Irritation:**
- Causes skin irritation. Prolong exposure may cause severe skin irritation.
- 11.4 Serious Eye Damage/Irritation:**
- Causes serious eye irritation
- 11.5 Respiratory Organ or Skin Sensitisation:**
- None.
- 11.6 Germ Cell Mutagenicity:**
- None.
- 11.7 Carcinogenicity:**
- None.
- 11.8 Reproductive Toxicity:**
- None.
- 11.9 Specific Target Organ Toxicity:**
- None.
- 11.10 Aspiration Hazard**
- Not applicable.

SECTION 12: ECOLOGICAL INFORMATION

- 12.1 Ecotoxicity of Product Mixture:**
- No data available.

Issue Date: 26 Aug 2019
 Version No.: 02 (Supersedes Version: 01)
 Last Revision Date: 11 Jun 2019
 Product No.: -

Page 6 of 7

12.2 Ecotoxicity on Ingredients:

Chemical Name	CAS No.	Fish Toxicity	Marine Organism
Sodium metasilicate	6834-92-0	210 mg/L (96 hrs)	Brachydanio rerio

12.3 Persistence and Degradability:

- No data on possible environmental effects have been found.

12.4 Bioaccumulative Potential:

- No data available on bioaccumulation.

12.5 Mobility:

- The product is water soluble and may spread in water systems.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal Method in Singapore:

- Dispose off in accordance to the Environmental Public Health (Toxic Industrial Waste) Regulations under the Environmental Protection and Management Act (EPMA).

13.2 Disposal Method Overseas:

- Dispose off in accordance with all applicable local or national regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 Land (ADR):

- UN Number: UN3266
- Class: 8, Corrosive
- Packing Group: III
- Proper Shipping Name: Corrosive liquid, basic, inorganic, n.o.s. (sodium metasilicate).
- Subsidiary Risk: None

14.2 Sea (IMDG):

- UN Number: UN3266
- Class: 8, Corrosive
- Packing Group: III
- Proper Shipping Name: Corrosive liquid, basic, inorganic, n.o.s. (sodium metasilicate).
- Subsidiary Risk: None
- Marine Pollutant (Yes/No): No
- Packing Instructions: P001 / LP01
- EmS (Emergency Schedule): F-A, S-B
- Limited Quantity: 20L
- Further Information: Do not allow any contact with light metals - danger of corrosion.

14.3 Sea (Annex II of MARPOL 73/78 and the IBC Code):

- Pollution Category: Not applicable.
- Ship Type: Not applicable.
- Product Name: Not applicable.

14.4 Air (IATA):

- UN Number: UN3266
- Class: 8, Corrosive
- Packing Group: III
- Proper Shipping Name: Corrosive liquid, basic, inorganic, n.o.s. (sodium metasilicate).
- Subsidiary Risk: None
- Label(s): Corrosive
- Passenger and Cargo Aircraft: Packing Instruction 818 Max. 5L
- Cargo Aircraft: Only: Packing Instruction 820 Max. 60L

Issue Date: 26 Aug 2019
Version No.: 02 (Supersedes Version: 01)
Last Revision Date: 11 Jun 2019
Product No.: -

Page 7 of 7

- Limited Quantity: 1L (Y818)
- Further Information: Do not allow any contact with light metals - danger of corrosion.

14.5 Special Precautions:

- Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1 Applicable Singapore Regulations:

- Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations:
This product is subject to the SDS, labelling, PEL and other requirements in the act/regulation.
- Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations:
This product is subject to the requirements in the act/regulation.
- Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives) Regulations:
This product is subject to the requirements in this regulation.

SECTION 16: OTHER INFORMATION

16.1 Issued By:

- FUJIFILM Asia Pacific Pte. Ltd.
- This SDS is prepared in accordance with Singapore Standard SS 586 : Part 3 : 2014.

16.2 Warranty:

- The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions.